























































































LED bulbs






















| Photo | Part No. | Color | Product Description | | |
|--|---|--|---|--|--|
|  | GB-1W: Size: 55 * 70mm (Diameter * Height), 45° light angle, built-in LED driver, working voltage: 220V | | | | |
| | GB-1W-WW |  2850-3500K | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 55-65lm, warm white | | |
| | GB-1W-W |  5650-7000K | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 70-80lm, pure white | | |
| | GB-1W-R |  620-630nm | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 45lm, red | | |
| | GS-1W-Y |  585-595nm | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 40lm, yellow | | |
| | GS-1W-B |  455-475nm | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 20lm, blue | | |
| | GS-1W-G |  515-535nm | Edison 1W power LED, 45° lens, built-in LED driver, 220V, 70lm, green | | |
|  | GB-MR16-1W: Size: 33 * 52mm (Diameter * Height), 15°, 30°, 60°or 90° light angle, built-in LED driver, working voltage: 12V AC/DC | | | | |
| | GB-MR16-1W-WW |  2850-3500K | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 55-65lm, warm white | | |
| | GB-MR16-1W-W |  5650-7000K | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 70-80lm, pure white | | |
| | GB-MR16-1W-R |  620-630nm | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 45lm, red | | |
| | GB-MR16-1W-Y |  585-595nm | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 45lm, yellow | | |
| | GB-MR16-1W-B |  455-475nm | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 20lm, blue | | |
| | GB-MR16-1W-G |  515-535nm | Edison 1W power LED, 30° lens, built-in LED driver, 12V, 70lm, green | | |

| Photo | Part No. | Color | Product Description |
|--|--|---|---|
|  | GB-3W: Size: 50 * 100mm (Diameter * Height), 140° light angle, built-in led driver, working voltage: 220V | | |
| | GB-3W-01-WW |  | 2850-3500K Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 165-195lm, warm white |
| | GB-3W-01-W |  | 5650-7000K Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 210-240lm, pure white |
| | GB-3W-01-R |  | 620-630nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 120-140lm, red |
| | GB-3W-01-Y |  | 585-595nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 110-130lm, yellow |
| | GB-3W-01-B |  | 455-475nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 40-60lm, blue |
| | GB-3W-01-G |  | 515-535nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 190-220lm, green |
|  | GB-3W-02: Size: 60 * 110mm (Diameter * Height). 45° light angle, built-in led driver, working voltage: 220V | | |
| | GB-3W-02-WW |  | 2850-3500K Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 100lm, warm white |
| | GB-3W-02-W |  | 5650-7000K Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 120lm, pure white |
| | GB-3W-02-R |  | 620-630nm Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 80lm, red |
| | GB-3W-02-Y |  | 585-595nm Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 85lm, yellow |
| | GB-3W-02-B |  | 455-475nm Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 30lm, blue |
| | GB-3W-02-G |  | 515-535nm Edison 1PC 3W power LED, 45°, built-in LED driver, 220V, 120lm, green |
|  | GB-3W-03: Size: 60 * 110mm (Diameter * Height). 140° light angle, built-in led driver, working voltage: 220V | | |
| | GB-3W-03-WW |  | 2850-3500K Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 165-195lm, warm white |
| | GB-3W-03-W |  | 5650-7000K Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 210-240lm, pure white |
| | GB-3W-03-R |  | 620-630nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 120-140lm, red |
| | GB-3W-03-Y |  | 585-595nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 110-130lm, yellow |
| | GB-3W-03-B |  | 455-475nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 40-60lm, blue |
| | GB-3W-03-G |  | 515-535nm Edison 3PCS 1W power LED, 140°, built-in LED driver, 220V, 190-220lm, green |

| Photo | Part No. | Color | Product Description | | |
|--|--|---|---------------------|--|--|
|  | GB-4W: Size: 60 * 110mm (Diameter * Height). 140° light angle, built-in led driver, working voltage: 220V | | | | |
| | GB-4W-WW |  | 2850-3500K | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 220-260lm, warm white | |
| | GB-4W-W |  | 5650-7000K | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 280-320lm, pure white | |
| | GB-4W-R |  | 620-630nm | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 160-180lm, red | |
| | GB-4W-Y |  | 585-595nm | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 150-170lm, yellow | |
| | GB-4W-B |  | 455-475nm | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 60-80lm, blue | |
| | GB-4W-G |  | 515-535nm | Edison 4pcs 1W power LED, 140°, built-in led driver, 220V, 250-270lm, green | |
|  | GB-5W-01: Size: 63 * 93mm (Diameter * Height). 30° light angle, built-in led driver, working voltage: 220V | | | | |
| | GB-5W-01-WW |  | 2850-3500K | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 275-325lm, warm white | |
| | GB-5W-01-W |  | 5650-7000K | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 350-400lm, pure white | |
| | GB-5W-01-R |  | 620-630nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 200-220lm, red | |
| | GB-5W-01-Y |  | 585-595nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 180-200lm, yellow | |
| | GB-5W-01-B |  | 455-475nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 70-80lm, blue | |
| | GB-5W-01-G |  | 515-535nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 320-340lm, green | |
|  | GS-5W-02: Size: 62 * 95mm (Diameter * Height). 30° light angle, built-in led driver, working voltage: 220V | | | | |
| | GS-5W-02-WW |  | 2850-3500K | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 275-325lm, warm white | |
| | GS-5W-02-W |  | 5650-7000K | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 350-400lm, pure white | |
| | GS-5W-02-R |  | 620-630nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 200-220lm, red | |
| | GS-5W-02-Y |  | 585-595nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 180-200lm, yellow | |
| | GS-5W-02-B |  | 455-475nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 70-80lm, blue | |
| | GS-5W-02-G |  | 515-535nm | Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 320-340lm, green | |










| Photo | Part No. | Color | Product Description |
|--|--|---|---|
|  | GB-5W-03: Size: 62 * 95mm (Diameter * Height). 30° light angle, built-in led driver, working voltage: 220V | | |
| | GB-5W-03-WW |  | 2850-3500K Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 275-325lm, warm white |
| | GB-5W-03-W |  | 5650-7000K Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 350-400lm, pure white |
| | GB-5W-03-R |  | 620-630nm Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 200-220lm, red |
| | GB-5W-03-Y |  | 585-595nm Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 180-200lm, yellow |
| | GB-5W-03-B |  | 455-475nm Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 70-80lm, blue |
| | GB-5W-03-G |  | 515-535nm Edison 5pcs 1W power LED, 30°, built-in led driver, 220V, 320-340lm, green |
|  | GB-5W-04: Size: 60 * 110mm (Diameter * Height). 140° light angle, built-in led driver, working voltage: 220V | | |
| | GB-5W-04-WW |  | 2850-3500K Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 275-325lm, warm white |
| | GB-5W-04-W |  | 5650-7000K Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 350-400lm, pure white |
| | GB-5W-04-R |  | 620-630nm Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 200-220lm, red |
| | GB-5W-04-Y |  | 585-595nm Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 180-200lm, yellow |
| | GB-5W-04-B |  | 455-475nm Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 70-80lm, blue |
| | GB-5W-04-G |  | 515-535nm Edison 5pcs 1W power LED, 140°, built-in led driver, 220V, 320-340lm, green |
|  | GB-6W-01: Size: 95 * 110mm (Diameter * Height). 140° light angle, built-in led driver, working voltage: 220V | | |
| | GB-6W-01-WW |  | 2850-3500K Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 330-390lm, warm white |
| | GB-6W-01-W |  | 5650-7000K Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 420-480lm, pure white |
| | GB-6W-01-R |  | 620-630nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 240-260lm, red |
| | GB-6W-01-Y |  | 585-595nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 220-240lm, yellow |
| | GB-6W-01-B |  | 455-475nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 80-90lm, blue |
| | GB-6W-01-G |  | 515-535nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 360-380lm, green |













| Photo | Part No. | Color | Product Description |
|--|---|---|---|
|  | GB-6W-02: Size: 70 * 120mm (Diameter * Height). 140° light angle, built-in led driver, working voltage: 220V | | |
| | GB-6W-02-WW |  | 2850-3500K Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 330-390lm, warm white |
| | GB-6W-02-W |  | 5650-7000K Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 420-480lm, pure white |
| | GB-6W-02-R |  | 620-630nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 240-260lm, red |
| | GB-6W-02-Y |  | 585-595nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 220-240lm, yellow |
| | GB-6W-02-B |  | 455-475nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 80-90lm, blue |
| | GB-6W-02-G |  | 515-535nm Edison 6pcs 1W power LED, 140°, built-in led driver, 220V, 360-380lm, green |
|  | GB-3W-G45: Size: 45 * 100mm (Diameter * Height). 180° light angle, built-in led driver, working voltage: 220V, base: E14, E26 & E27 available | | |
| | GB-3W-G45-WW |  | 2850-3500K Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 100lm, warm white |
| | GB-3W-G45-W |  | 5650-7000K Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 120lm, pure white |
| | GB-3W-G45-R |  | 620-630nm Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 80lm, red |
| | GB-3W-G45-Y |  | 585-595nm Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 85lm, yellow |
| | GB-3W-G45-B |  | 455-475nm Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 30lm, blue |
| | GB-3W-G45-G |  | 515-535nm Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 120lm, green |
|  | GB-3W-G50: Size: 50 * 100mm (Diameter * Height). 180° light angle, built-in led driver, working voltage: 220V, base: E14, E26 & E27 available | | |
| | GB-3W-G50-WW |  | 2850-3500K Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 100lm, warm white |
| | GB-3W-G50-W |  | 5650-7000K Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 120lm, pure white |
| | GB-3W-G50-R |  | 620-630nm Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 80lm, red |
| | GB-3W-G50-Y |  | 585-595nm Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 85lm, yellow |
| | GB-3W-G50-B |  | 455-475nm Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 30lm, blue |
| | GB-3W-G50-G |  | 515-535nm Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 120lm, green |













| Photo | Part No. | Color | Product Description | | |
|---|---|---|---------------------|---|--|
|  | GB-3W-G60: Size: 60 * 115mm (Diameter * Height). 180° light angle, built-in led driver, working voltage: 220V, base: E14, E26 & E27 available | | | | |
| | GB-3W-G60-WW |  | 2850-3500K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 100lm, warm white | |
| | GB-3W-G60-W |  | 5650-7000K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 120lm, pure white | |
| | GB-3W-G60-R |  | 620-630nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 80lm, red | |
| | GB-3W-G60-Y |  | 585-595nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 85lm, yellow | |
| | GB-3W-G60-B |  | 455-475nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 30lm, blue | |
| | GB-3W-G60-G |  | 515-535nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 120lm, green | |
|  | GB-3W-G70: Size: 70 * 130mm (Diameter * Height). 180° light angle, built-in led driver, working voltage: 220V, base: E14, E26 & E27 available | | | | |
| | GB-3W-G70-WW |  | 2850-3500K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 100lm, warm white | |
| | GB-3W-G70-W |  | 5650-7000K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 120lm, pure white | |
| | GB-3W-G70-R |  | 620-630nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 80lm, red | |
| | GB-3W-G70-Y |  | 585-595nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 85lm, yellow | |
| | GB-3W-G70-B |  | 455-475nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 30lm, blue | |
| | GB-3W-G70-G |  | 515-535nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 120lm, green | |
|  | GB-3W-C: Size: 45 * 130mm (Diameter * Height). 180° light angle, built-in led driver, working voltage: 220V, base: E14, E26 & E27 available | | | | |
| | GB-3W-C-WW |  | 2850-3500K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 100lm, warm white | |
| | GB-3W-C-W |  | 5650-7000K | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 120lm, pure white | |
| | GB-3W-C-R |  | 620-630nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 80lm, red | |
| | GB-3W-C-Y |  | 585-595nm | Edison 1pc 3W power LED, 180°, built-in led driver, 220V, 85lm, yellow | |
| | GB-3W-C-B |  | 455-475nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 30lm, blue | |
| | GB-3W-C-G |  | 515-535nm | Edison 1pcs 3W power LED, 180°, built-in led driver, 220V, 120lm, green | |



























LED down light













| Photo | Part No. | Color | Product Description | | |
|--|--|--|--|--|--|
|  | GC-1W-01: Size: 65 * 50mm (Diameter * Height), 30° or 45° lens, 350mA constant current LED driver | | | | |
| | GC-1W-01-WW |  2850-3500K | Edison 1W power LED, 30° or 45° lens, 350mA constant current led driver, 55-65lm, warm white | | |
| | GC-1W-01-W |  5650-7000K | Edsion 1W power LED, 30° or 45° lens, 350mA constant led driver, 70-80lm, pure white | | |
|  | GC-1W-02: Size: 58 * 45mm (Diameter * Height), 15°, 20°, 30°, 45° or 60° lens, 350mA constant led driver | | | | |
| | GC-1W-02-WW |  2850-3500K | Edison 1W power LED, 30° or 45° lens, 350mA constant current led driver, 55-65lm, warm white | | |
| | GC-1W-02-W |  5650-7000K | Edsion 1W power LED, 30° or 45° lens, 350mA constant led driver, 70-80lm, pure white | | |
|  | GC-1W-03: Size: 75 * 40mm (Diameter * Height). 30° lens, 350mA constant led driver | | | | |
| | GC-1W-03-WW |  2850-3500K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 55-65lm, warm white | | |
| | GC-1W-03-W |  5650-7000K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 70-80lm, pure white | | |








| Photo | Part No. | Color | Product Description | |
|--|--|--|---|--|
|  | GC-1W-04: Size: 54 * 30mm (Diameter * Height). 30°or 60° lens, 350mA constant led driver | | | |
| | GC-1W-04-WW |  2850-3500K | Edison 1W power LED, 30°or 60°lens, 350mA constant current led driver, 55-65lm, warm white | |
| | GC-1W-04-W |  5650-7000K | Edison 1W power LED, 30°or 60° lens, 350mA constant current led driver, 70-80lm, pure white | |
|  | GC-1W-05: Size: 67 * 65mm (Diameter * Height). 45°or 60° lens, 350mA constant led driver | | | |
| | GC-1W-05-WW |  2850-3500K | Edison 1W power LED, 45°or 60°lens, 350mA constant current led driver, 55-65lm, warm white | |
| | GC-1W-05-W |  5650-7000K | Edison 1W power LED, 45°or 60° lens, 350mA constant current led driver, 70-80lm, pure white | |
|  | GC-1W-06: Size: 80 * 45mm (Diameter * Height). 30° lens, 350mA constant led driver | | | |
| | GC-1W-06-WW |  2850-3500K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 55-65lm, warm white | |
| | GC-1W-06-W |  5650-7000K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 70-80lm, pure white | |
|  | GC-1W-07: Size: 52 * 24mm (Diameter * Height). 60° lens, 350mA constant led driver | | | |
| | GC-1W-07-WW |  2850-3500K | Edison 1W power LED, 60° lens, 350mA constant current led driver, 55-65lm, warm white | |
| | GC-1W-07-W |  5650-7000K | Edison 1W power LED, 60° lens, 350mA constant current led driver, 70-80lm, pure white | |

| Photo | Part No. | Color | Product Description | | |
|--|--|--|--|--|--|
|  | GC-1W-08: Size: 34 * 46mm (Diameter * Height). 30° lens, 350mA constant led driver | | | | |
| | GC-1W-08-WW |  2850-3500K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 55-65lm, warm white | | |
| | GC-1W-08-W |  5650-7000K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 70-80lm, pure white | | |
|  | GC-1W-09: Size: 61 * 61 * 40mm (Length * Width * Height). 30° lens, 350mA constant led driver | | | | |
| | GC-1W-09-WW |  2850-3500K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 55-65lm, warm white | | |
| | GC-1W-09-W |  5650-7000K | Edison 1W power LED, 30° lens, 350mA constant current led driver, 70-80lm, pure white | | |
|  | GC-3W-01: Size: 65 * 50mm (Diameter * Height), 30° or 45° lens, 700mA constant current LED driver | | | | |
| | GC-3W-01-WW |  2850-3500K | Edison 3W power LED, 30° or 45° lens, 700mA constant current led driver, 100lm, warm white | | |
| | GC-3W-01-W |  5650-7000K | Edsion 3W power LED, 30° or 45° lens, 700mA constant current led driver, 120lm, pure white | | |
|  | GC-3W-02: Size: 58 * 45mm (Diameter * Height), 15°, 20°, 30°, 45° or 60° lens, 700mA constant led driver | | | | |
| | GC-3W-02-WW |  2850-3500K | Edison 3W power LED, 30° or 45° lens, 700mA constant current led driver, 100lm, warm white | | |
| | GC-3W-02-W |  5650-7000K | Edsion 3W power LED, 30° or 45° lens, 700mA constant led driver, 120lm, pure white | | |










| Photo | Part No. | Color | Product Description | | |
|--|---|---|---------------------|--|--|
|  | GC-3W-03: Size: 75 * 40mm (Diameter * Height). 30° lens, 700mA constant led driver | | | | |
| | GC-3W-03-WW |  | 2850-3500K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-03-W |  | 5650-7000K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3W-04: Size: 54 * 30mm (Diameter * Height). 30° or 60° lens, 700mA constant led driver | | | | |
| | GC-3W-04-WW |  | 2850-3500K | Edison 3W power LED, 30° or 60° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-04-W |  | 5650-7000K | Edison 3W power LED, 30° or 60° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3W-05: Size: 67 * 65mm (Diameter * Height). 45° or 60° lens, 700mA constant led driver | | | | |
| | GC-3W-05-WW |  | 2850-3500K | Edison 3W power LED, 45° or 60° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-05-W |  | 5650-7000K | Edison 3W power LED, 45° or 60° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3W-06: Size: 80 * 45mm (Diameter * Height). 30° lens, 700mA constant led driver | | | | |
| | GC-3W-06-WW |  | 2850-3500K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-06-W |  | 5650-7000K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 120lm, pure white | |













| Photo | Part No. | Color | Product Description | | |
|--|---|---|---------------------|---|--|
|  | GC-3W-07: Size: 52 * 24mm (Diameter * Height). 60° lens, 700mA constant led driver | | | | |
| | GC-3W-07-WW |  | 2850-3500K | Edison 3W power LED, 60° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-07-W |  | 5650-7000K | Edison 3W power LED, 60° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3W-08: Size: 34 * 46mm (Diameter * Height). 30° lens, 700mA constant led driver | | | | |
| | GC-3W-08-WW |  | 2850-3500K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-R-08-W |  | 5650-7000K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3W-09: Size: 61 * 61 * 40mm (Length * Width * Height). 30° lens, 700mA constant led driver | | | | |
| | GC-3W-09-WW |  | 2850-3500K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 100lm, warm white | |
| | GC-3W-09-W |  | 5650-7000K | Edison 3W power LED, 30° lens, 700mA constant current led driver, 120lm, pure white | |
|  | GC-3 * 1W-01: Size: 73 * 50mm (Diameter * Height), 45° or 60° lens, 350mA constant led driver | | | | |
| | GC-3 * 1W-01-WW |  | 2850-3500K | Edison 3pcs 1W power LED, 45°or 60°lens, 350mA constant current led driver, 165-195lm, warm white | |
| | GC-3 * 1W-01-W |  | 5650-7000K | Edison 3pcs 1W power LED, 45°or 60° lens, 350mA constant current led driver,210-240lm, pure white | |


| Photo | Part No. | Color | Product Description |
|--|--|--|---|
|  | GC-3 * 1W-02: Size: 90 * 78mm (Diameter * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-3 * 1W-02-WW |  2850-3500K | Edison 3pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,165-195lm,warm white |
| | GC-3 * 1W-02-W |  5650-7000K | Edison 3pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,210-240lm, pure white |
|  | GC-3 * 1W-03: Size: 175 * 94 * 50mm (Length * Width * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-3 * 1W-03-WW |  2850-3500K | Edison 6pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,330-390lm,warm white |
| | GC-3 * 1W-03-W |  5650-7000K | Edison 6pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,420-480lm, pure white |
|  | GC-3 * 1W-04: Size: 257 * 93 * 47mm (Length * Width * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-3 * 1W-04-WW |  2850-3500K | Edison 6pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,330-390lm,warm white |
| | GC-3 * 1W-04-W |  5650-7000K | Edison 6pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,420-480lm, pure white |
|  | GC-4 * 1W: Size: 91 * 70mm (Diameter * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-4 * 1W-WW |  2850-3500K | Edison 4pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,330-390lm,warm white |
| | GC-4 * 1W-W |  5650-7000K | Edison 4pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,280-320lm, pure white |

| Photo | Part No. | Color | Product Description |
|--|---|--|--|
|  | GC-6 * 1W: Size: 113 * 50mm (Diameter * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-6 * 1W-WW |  2850-3500K | Edison 6pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,330-390lm,warm white |
| | GC-6 * 1W-W |  5650-7000K | Edison 6pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,lm, pure white |
|  | GC-9 * 1W: Size: 125 * 60mm (Diameter * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-9 * 1W-WW |  2850-3500K | Edison 9pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,495-585lm,warm white |
| | GC-9 * 1W-W |  5650-7000K | Edison 9pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,630-720lm, pure white |
|  | GC-12 * 1W: Size: 135 * 70mm (Diameter * Height), 30°or 60° lens, 350mA constant led driver | | |
| | GC-12 * 1W-WW |  2850-3500K | Edison 12pcs 1W LED, 30°or 60°lens, 350mA constant current led driver,660-780lm,warm white |
| | GC-12 * 1W-W |  5650-7000K | Edison 12pcs 1W LED, 30°or 60° lens, 350mA constant current led driver,840-960lm, pure white |

LED Filament LED Bulb

| Item No. | Picture | Voltage | Power | CRI | PF | Color Temperature | Life-span | Lumens | Angle | Lamp size | Certificate | |
|-----------------|---|------------|-------|-----|----|-------------------|-----------|--------|-------|-----------|-------------|--|
| GL-C35-E14-2W-1 |  | 110V /220V | 2W | 80 | 50 | 2700K / 6000K | 20000H | 150lm | 320° | 99*35 | CE ROHS | |
| GL-C35-E14-2W-2 |  | 110V /220V | 2W | 80 | 50 | 2700K / 6000K | 20000H | 150lm | 320° | 104*35 | CE ROHS | |
| GL-C35-E14-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 340lm | 320° | 99*35 | CE ROHS | |
| GL-C35-E14-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 450lm | 320° | 99*35 | CE ROHS | |
| GL-A60-E27-2W |  | 110V /220V | 2W | 80 | 50 | 2700K / 6000K | 20000H | 150lm | 320° | 103*60 | CE ROHS | |
| GL-A60-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 340lm | 320° | 103*60 | CE ROHS | |
| GL-A60-E27-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 500lm | 320° | 103*60 | CE ROHS | |
| GL-A60-E27-8W |  | 110V /220V | 8W | 80 | 50 | 2700K / 6000K | 20000H | 750 lm | 320° | 103*60 | CE ROHS | |
| GL-G45-E27-2W |  | 110V /220V | 2W | 80 | 50 | 2700K / 6000K | 20000H | 150 lm | 320° | 103*60 | CE ROHS | |

| | | | | | | | | | | | | |
|----------------|---|------------|----|----|----|------------------|--------|--------|------|---------|---------|--|
| GL-G45-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 340 lm | 320° | 103*60 | CE ROHS | |
| GL-ST64-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 400 lm | 320° | 103*64 | CE ROHS | |
| GL-ST64-E27-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 720lm | 320° | 103*64 | CE ROHS | |
| GL-ST64-E27-8W |  | 110V /220V | 8W | 80 | 50 | 2700K / 6000K | 20000H | 900 lm | 320° | 103*64 | CE ROHS | |
| GL-G80-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 400lm | 320° | 103*80 | CE ROHS | |
| GL-G80-E27-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 720lm | 320° | 103*80 | CE ROHS | |
| GL-G80-E27-8W |  | 110V /220V | 8W | 80 | 50 | 2700K / 6000K | 20000H | 900 lm | 320° | 103*80 | CE ROHS | |
| GL-G95-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 400lm | 320° | 103*95 | CE ROHS | |
| GL-G95-E27-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 720lm | 320° | 103*95 | CE ROHS | |
| GL-G95-E27-8W |  | 110V /220V | 8W | 80 | 50 | 2700K / 6000K | 20000H | 900 lm | 320° | 103*95 | CE ROHS | |
| GL-G125-E27-4W |  | 110V /220V | 4W | 80 | 50 | 2700K / 6000K | 20000H | 400lm | 320° | 103*125 | CE ROHS | |
| GL-G125-E27-6W |  | 110V /220V | 6W | 80 | 50 | 2700K / 6000K | 20000H | 720lm | 320° | 103*125 | CE ROHS | |

| | | | | | | | | | | | | |
|----------------|--|------------|----|----|----|------------------|--------|--------|------|---------|---------|--|
| GL-G125-E27-8W |  | 110V /220V | 8W | 80 | 50 | 2700K / 6000K | 20000H | 900 lm | 320° | 103*125 | CE ROHS | |
|----------------|--|------------|----|----|----|------------------|--------|--------|------|---------|---------|--|






















More Customized Requirements:






















1. Add Logo
2. Matte cover
3. Wide range of Voltage
4. Dimmable
5. High Level Package Protection



LED spot light

| Photo | Part No. | Color | Product Description | | |
|-------|---|------------|---|--|--|
| | GS-1W-01: Size: 65 * 110mm (Diameter * Height). 120° lens, need 350mA constant current led driver to work | | | | |
| | GS-1W-01-WW | 2850-3500K | Edison 1W power LED, 120° lens, without led driver built-in, 55-65lm, warm white | | |
| | GS-1W-01-W | 5650-7000K | Edison 1W power LED, 120° lens, without led driver built-in, 80-90lm, pure white | | |
| | GS-1W-01-R | 620-630nm | Edison 1W power LED, 120° lens, without led driver built-in, 45lm, red | | |
| | GS-1W-01-Y | 585-595nm | Edison 1W power LED, 120° lens, without led driver built-in, 45lm, yellow | | |
| | GS-1W-01-B | 455-475nm | Edison 1W power LED, 120° lens, without led driver built-in, 20lm, blue | | |
| | GS-1W-01-G | 515-535nm | Edison 1W power LED, 120° lens, without led driver built-in, 70lm, green | | |
| | GS-1W-02: Size: 65 * 120mm (Diameter * Height). 15°, 30°, 60°or 90° lens, need 350mA constant led driver | | | | |
| | GS-1W-02-WW | 2850-3500K | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 55-65lm, warm white | | |
| | GS-1W-02-W | 5650-7000K | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 80-90lm, pure white | | |
| | GS-1W-02-R | 620-630nm | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 45lm, red | | |
| | GS-1W-02-Y | 585-595nm | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 45lm, yellow | | |
| | GS-1W-02-B | 455-475nm | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 20lm, blue | | |
| | GS-1W-02-G | 515-535nm | Edison 1W power LED, 15°,30°,60°or 90° lens, without led driver built-in, 70lm, yellow | | |

| Photo | Part No. | Color | Product Description |
|--|--|---|---|
|  | GS-1W-03: Size: 14 * 58mm (Diameter * Height). 15° lens, need 350mA constant current led driver | | |
| | GS-1W-03-WW |  | 2850-3500K Edison 1W power LED, 15° lens, without led driver built-in, 55-65lm, warm white |
| | GS-1W-03-W |  | 5650-7000K Edison 1W power LED, 15° lens, without led driver built-in, 80-90lm, pure white |
| | GS-1W-03-R |  | 620-630nm Edison 1W power LED, 15° lens, without led driver built-in, 45lm, red |
| | GS-1W-03-Y |  | 585-595nm Edison 1W power LED, 15° lens, without led driver built-in, 45lm, yellow |
| | GS-1W-03-B |  | 455-475nm Edison 1W power LED, 15° lens, without led driver built-in, 20lm, blue |
| | GS-1W-03-G |  | 515-535nm Edison 1W power LED, 15° lens, without led driver built-in, 70lm, green |
|  | GS-1W-04: Size: 39 * 12mm (Diameter * Height). 120° lens, need 350mA constant current led driver | | |
| | GS-1W-04-WW |  | 2850-3500K Edison 1W power LED, 120° lens, without led driver built-in, 55-65lm, warm white |
| | GS-1W-04-W |  | 5650-7000K Edison 1W power LED, 120° lens, without led driver built-in, 80-90lm, pure white |
| | GS-1W-04-R |  | 620-630nm Edison 1W power LED, 120° lens, without led driver built-in, 45lm, red |
| | GS-1W-04-Y |  | 585-595nm Edison 1W power LED, 120° lens, without led driver built-in, 45lm, yellow |
| | GS-1W-04-B |  | 455-475nm Edison 1W power LED, 120° lens, without led driver built-in, 20lm, blue |
| | GS-1W-04-G |  | 515-535nm Edison 1W power LED, 120° lens, without led driver built-in, 70lm, green |
|  | GS-1W-05: Size: 32 * 52mm (Diameter * Height). 15°, 30°, 60° or 90° lens, built-in 350mA constant current led driver | | |
| | GS-1W-05-WW |  | 2850-3500K Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 55-65lm, warm white |
| | GS-1W-05-W |  | 5650-7000K Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 80-90lm, pure white |
| | GS-1W-05-R |  | 620-630nm Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 45lm, red |
| | GS-1W-05-Y |  | 585-595nm Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 45lm, yellow |
| | GS-1W-05-B |  | 455-475nm Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 20lm, blue |
| | GS-1W-05-G |  | 515-535nm Edison 1W power LED, 15°, 30°, 60° or 90° lens, built-in led driver, 70lm, green |

| Photo | Part No. | Color | Product Description |
|--|---|---|---|
|  | GS-1W-06: Size: 65 * 120mm (Diameter * Height). 15°, 30°,60°or 90° lens, need 350mA constant current led driver | | |
| | GS-1W-06-WW |  | 2850-3500K Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 55-65lm, warm white |
| | GS-1W-06-W |  | Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 80-90lm, pure white |
| | GS-1W-06-R |  | Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 45lm, red |
| | GS-1W-06-Y |  | Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 45lm, yellow |
| | GS-1W-06-B |  | Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 20lm, blue |
| | GS-1W-06-G |  | Edison 1W power LED, 15°,30°,60°or 90°lens, without led driver built-in, 70lm, green |
|  | GS-1W-07: Size: 60 * 60 * 140mm (Length * Width * Height), 120°lens, built-in 350mA constant current LED driver | | |
| | GS-1W-07-WW |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 55-65lm, warm white |
| | GS-1W-07-W |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 80-90lm, pure white |
| | GS-1W-07-R |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 45lm, red |
| | GS-1W-07-Y |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 45lm, yellow |
| | GS-1W-07-B |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 20lm, blue |
| | GS-1W-07-G |  | Edison 1W power LED, 120° lens, built-in 350mA constant current LED driver, 70lm, green |
|  | GS-1W-08: Size: 70 * 45 * 65mm (Length * Width * Height), 90°lens, need 350mA constant current led driver to work | | |
| | GS-1W-08-WW |  | Edison 1W power LED, 120° lens, without led driver built-in, 55-65lm, warm white |
| | GS-1W-08-W |  | Edison 1W power LED, 120° lens, without led driver built-in, 80-90lm, pure white |
| | GS-1W-08-R |  | Edison 1W power LED, 120° lens, without led driver built-in, 45lm, red |
| | GS-1W-08-Y |  | Edison 1W power LED, 120° lens, without led driver built-in, 45lm, yellow |
| | GS-1W-08-B |  | Edison 1W power LED, 120° lens, without led driver built-in, 20lm, blue |
| | GS-1W-08-G |  | Edison 1W power LED, 120° lens, without led driver built-in, 70lm, green |




Full Nano Plastic T8 Tube

- Patent Nano Plastic Diffuser
- Not Bent after working long time
- Soft lighting, no glare
- Thin like paper but high intensity
- V0 fireproof



1. PCB board is aluminum
2. Regular package is color box or white box without any logo
3. Accept laser marking logo on surface, accept custom box package

Full Plastic T8 LED Tube, 2 years warranty

| Series | Item No. | LED Type&Qty | Driver | Input V | Power | Lumen | Beam Angle | CCT | CRI | PF | |
|--|-----------------|--|--------------------------------------|----------------|-------|-----------|------------|------------|-----|------|---|
| Economic Series Ra>70, PF>0.6 AC110V or AC220V | GL-T8PC60E-9W | SMD2835 46pcs | constant current non-isolated Driver | AC110V or 220V | 9W | 800lm±5% | 270° | 2800-6500K | >70 | >0.6 | |
| | GL-T8PC120E-18W | SMD2835 96pcs | | | 18W | 1650lm±5% | | | | | |
| | GL-T8PC240E-36W | SMD2835 192pcs | | | 36W | 3000lm±5% | | | | | |
| High PF Series Ra>70, PF>0.9 AC85-265V | GL-T8PC60H-9W | SMD2835 46pcs | constant current non-isolated Driver | AC85-265V | 9W | 800lm±5% | 270° | 2800-6500K | >70 | >0.9 | |
| | GL-T8PC120H-18W | SMD2835 96pcs | | | 18W | 1650lm±5% | | | | | |
| | GL-T8PC150H-23W | SMD2835 120pcs | | | 23W | 2000lm±5% | | | | | |
| | GL-T8PC240H-36W | SMD2835 192pcs | | | 36W | 3000lm±5% | | | | | |
| High RA/PF Series Ra>80, PF>0.9 AC85-265V | GL-T8PC60D-9W | SMD2835 46pcs | constant current non-isolated Driver | AC85-265V | 9W | 900lm±5% | 270° | 2800-6500K | >80 | >0.9 | |
| | GL-T8PC120D-18W | SMD2835 96pcs | | | 18W | 1800lm±5% | | | | | |
| | GL-T8PC150D-23W | SMD2835 120pcs | | | 23W | 2300lm±5% | | | | | |
| | GL-T8PC240D-36W | SMD2835 192pcs | | | 36W | 3500lm±5% | | | | | |
| Package Details | 60cm | Packed in box, 50pcs/ctn, 7.6kg/ctn, ctn size:63*33*17.5cm | | | | | | | | |  |
| | 120cm | Packed in box, 50pcs/ctn, 13.2kg/ctn, ctn size: 124*33*17.5cm | | | | | | | | | |
| | 150cm | Packed in box, 50pcs/ctn, 15.3kg/ctn, ctn size: 155*33*17.5cm | | | | | | | | | |
| | 240cm | Packed in thick paper tube, 25pcs/ctn, ctn size: 250*20*17.5cm | | | | | | | | | |



LED tube compare to florescent tube , energy saving comparation

| | | T8 - 1.2m florescent tube | T8 - 1.2m LED tube | T5 - 0.6m florescent tube | T5 - 0.6m LED tube |
|---|----------|--------------------------------------|-------------------------------|--------------------------------------|-------------------------------|
| QTY (pcs) | | 100 | | 100 | |
| working life (hours) | | 6000 | 25000 | 6000 | 25000 |
| watt / pc | | 41 | 18 | 25 | 9 |
| (KW) | | 4.1 | 1.8 | 2.5 | 0.9 |
| working hour/day | | 8 | | 8 | |
| power consumption (KW) | 1 day | 32.8 | 14.4 | 20 | 7.2 |
| | 1 month | 984 | 432 | 600 | 216 |
| | 3 months | 2952 | 1296 | 1800 | 648 |
| | 6 months | 5904 | 2592 | 3600 | 1296 |
| | 1 year | 11808 | 5184 | 7200 | 2592 |
| | 3 years | 35424 | 15552 | 21600 | 7776 |
| electric charge per kilowatt hour | | 0.12 | | 0.12 | |
| electric charge | 1 day | \$3.94 | \$1.73 | \$2.40 | \$0.86 |
| | 1 month | \$118.08 | \$51.84 | \$72.00 | \$25.92 |
| | 3 months | \$354.24 | \$155.52 | \$216.00 | \$77.76 |
| | 6 months | \$708.48 | \$311.04 | \$432.00 | \$155.52 |
| | 1 year | \$1,416.96 | \$622.08 | \$864.00 | \$311.04 |
| | 3 years | \$4,250.88 | \$1,866.24 | \$2,592.00 | \$933.12 |
| saving fee of led tube than florescent tube | 1 day | \$2.21 | | \$1.54 | |
| | 1 month | \$66.24 | | \$46.08 | |
| | 3 months | \$198.72 | | \$138.24 | |
| | 6 months | \$397.44 | | \$276.48 | |
| | 1 year | \$794.88 | | \$552.96 | |
| | 3 years | \$2,384.64 | | \$1,658.88 | |
| maintain time (3 years) | | 2 | 0 | 2 | 0 |
| maintenance cost (\$1.50/time) | | \$279 | 0 | \$279 | 0 |
| total saving cost for 3 years | | \$2,663.64 | 0 | \$1,937.88 | 0 |





| Bulb Type | \$ savings % | Life Comp | Life Hours |
|---------------|--------------|-----------|------------|
| T8 Florescent | 0 | 1 | 6000 |
| T5 Florescent | 39% | 1 | 6000 |
| T8 LED | 56% | 4.17 | 25000 |
| T5 LED | 78% | 4.17 | 25000 |






LED T5 compare to T8 , energy comparison















| Item | Power | Lumen |
|--|-------|--------|
| T5 | 28W | 2520LM |
| T8 | 30W | 2200LM |
| T5 will be brighter but power will be lower. | | |









LED Panel Lights

| Item No. | Picture | Specification | CRI | Lumen |
|---------------------------------------|---|--|-----------|-----------------|
| LED Slim Recessed Panel Lights | | | | |
| GL-THD01-3W |  | LED round slim panel lamp, 3w, lamp size \varnothing 85mm, hole size: \varnothing 70mm, 15*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 150lm \pm 5% |
| GL-THD01-6W | | LED round slim panel lamp, 6w, lamp size \varnothing 120mm, hole size: \varnothing 100mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% |
| GL-THD01-9W | | LED round slim panel lamp, 9w, lamp size \varnothing 147mm, hole size: \varnothing 132mm, 45*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 540lm \pm 5% |
| GL-THD01-12W | | LED round slim panel lamp, 12w, lamp size \varnothing 170mm, hole size: \varnothing 150mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 740lm \pm 5% |
| GL-THD01-15W | | LED round slim panel lamp, 15w, lamp size \varnothing 190mm, hole size: \varnothing 175mm, 75*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 950lm \pm 5% |
| GL-THD01-18W | | LED round slim panel lamp, 18w, lamp size \varnothing 220mm, hole size: \varnothing 200mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1260lm \pm 5% |
| GL-THD01-24W | | LED round slim panel lamp, 24w, lamp size \varnothing 300mm, hole size: \varnothing 280mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1550lm \pm 5% |
| GL-THD02-3W |  | LED square slim panel lamp, 3w, lamp size 85 *85mm, hole size: 70 *70mm, 15*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 150lm \pm 5% |
| GL-THD02-6W | | LED square slim panel lamp, 6w, lamp size 120 *120mm, hole size: 100 *100mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% |
| GL-THD02-9W | | LED square slim panel lamp, 9w, lamp size 147 *147mm, hole size: 132 *132mm, 45*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 540lm \pm 5% |
| GL-THD02-12W | | LED square slim panel lamp, 12w, lamp size 170 *170mm, hole size: 150 *150mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 740lm \pm 5% |
| GL-THD02-15W | | LED square slim panel lamp, 15w, lamp size 190 *190mm, hole size: 175 *175mm, 75*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 950lm \pm 5% |
| GL-THD02-18W | | LED square slim panel lamp, 18w, lamp size 220 *220mm, hole size: 200 *200mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1260lm \pm 5% |
| GL-THD02-24W | | LED square slim panel lamp, 24w, lamp size 300 *300mm, hole size: 280 *280mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1550lm \pm 5% |
| LED SMD Glass Panel Lights | | | | |
| GL-BLR-6W |  | LED SMD round glass down light, 6w, lamp size \varnothing 100mm, hole size: \varnothing 75mm, 12*SMD5730 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% |
| GL-BLR-12W | | LED SMD round glass down light, 12w, lamp size \varnothing 160mm, hole size: \varnothing 120mm, 24*SMD5730 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 750lm \pm 5% |
| GL-BLR-18W | | LED SMD round glass down light, 18w, lamp size \varnothing 200mm, hole size: \varnothing 160mm, 36*SMD5730 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1260lm \pm 5% |
| GL-BLS-6W |  | LED SMD square glass down light, 6w, lamp size 100 *100mm, hole size: 75 *75mm, 12*SMD5730 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% |
| GL-BLS-12W | | LED SMD square glass down light, 12w, lamp size 160 *160mm, hole size: 120 *120mm, 24*SMD5730 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 750lm \pm 5% |
| GL-BLS-18W | | LED SMD square glass down light, 18w, lamp size 200 *200mm, hole size: 160 *160mm, 36*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1260lm \pm 5% |

| LED COB Glass Panel Lights | | | | | |
|----------------------------------|---|---|-----------|-----------------|--|
| GL-BLR-6W |  | LED COB round glass down light, 6w, lamp size \varnothing 100mm, hole size: \varnothing 75mm, 12*SMD5730 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-BLR-12W | | LED COB round glass down light, 12w, lamp size \varnothing 160mm, hole size: \varnothing 120mm, 24*SMD5730 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-BLR-18W | | LED COM round glass down light, 18w, lamp size \varnothing 200mm, hole size: \varnothing 160mm, 36*SMD5730 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 1260lm \pm 5% | |
| GL-BLS-6W |  | LED COB square glass down light, 6w, lamp size 100 *100mm, hole size: 75 *75mm, 12*SMD5730 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-BLS-12W | | LED COB square glass down light, 12w, lamp size 160 *160mm, hole size: 120 *120mm, 24*SMD5730 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-BLS-18W | | LED COB square glass down light, 18w, lamp size 200 *200mm, hole size: 160 *160mm, 36*SMD2835 , IP22, 30,000hrs operating life, AC220-240V input, 1 years warranty | ≥ 70 | 1260lm \pm 5% | |
| LED Surface Mounted Panel Lights | | | | | |
| GL-MGR-6W |  | LED round surface mounted lamp, 6w, lamp size \varnothing 120mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-MGR-12W | | LED round surface mounted lamp, 12w, lamp size \varnothing 170mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 720lm \pm 5% | |
| GL-MGR-18W | | LED round surface mounted lamp, 18w, lamp size \varnothing 225mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1200lm \pm 5% | |
| GL-MGR-24W | | LED round surface mounted lamp, 24w, lamp size \varnothing 300mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1500lm \pm 5% | |
| GL-MGR-30W | | LED round surface mounted lamp, 30w, lamp size \varnothing 400mm, 150*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 2200lm \pm 5% | |
| GL-MGR-36W | | LED round surface mounted lamp, 36w, lamp size \varnothing 500mm, 180*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 2620lm \pm 5% | |
| GL-MGR-48W | | LED round surface mounted lamp, 48w, lamp size \varnothing 600mm, 240*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 3460lm \pm 5% | |
| GL-MGS-6W |  | LED square surface mounted lamp, 6w, lamp size 120 *120mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-MGS-12W | | LED square surface mounted lamp, 12w, lamp size 170 *170mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-MGS-18W | | LED square surface mounted lamp, 18w, lamp size 225 *225mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1260lm \pm 5% | |
| GL-MGS-24W | | LED square surface mounted lamp, 24w, lamp size 300 *300mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 1550lm \pm 5% | |
| GL-MGS-36W | | LED square surface mounted lamp, 36w, lamp size 450*450mm, 180*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 2620lm \pm 5% | |
| GL-MGS-48W | | LED square surface mounted lamp, 48w, lamp size 600 *600mm, 240*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 3460lm \pm 5% | |
| GL-MGS-48W | | LED square surface mounted lamp, 48w, lamp size 300 *1200mm, 240*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥ 70 | 3460lm \pm 5% | |
| LED Flat Panel Lights | | | | | |
| GL-3060-24W |  | LED flat panel light, 24w, lamp size \varnothing 295*595mm, 90*SMD2835, San'an chip, IP22, AC220-240V input, 2 years warranty | ≥ 70 | 1920lm \pm 5% | |
| GL-6060-36W | | LED flat panel light, 36w, lamp size \varnothing 595*595mm, 180*SMD2835, San'an chip, IP22, AC220-240V input, 2 years warranty | ≥ 70 | 2880Lm \pm 5% | |
| GL-12030-36W | | LED flat panel light, 36w, lamp size \varnothing 295*1195mm, 180*SMD2835, San'an chip, IP22, AC220-240V input, 2 years warranty | ≥ 70 | 2880Lm \pm 5% | |
| GL-6060-48W | | LED flat panel light, 48w, lamp size \varnothing 595*595mm, 240*SMD2835, San'an chip, IP22, AC220-240V input, 2 years warranty | ≥ 70 | 3600lm \pm 5% | |
| GL-12030-48W | | LED flat panel light, 48w, lamp size \varnothing 295*1195mm, 240*SMD2835, San'an chip, IP22, AC220-240V input, 2 years warranty | ≥ 70 | 3600lm \pm 5% | |

| LED Two Color Panel Lights | | | | | |
|---------------------------------|---|---|-----|-----------|--|
| GL-BLR-3C-5W |  | LED Round Three-color Down Light; Size: Ø130mm; Cut-out: Ø110mm; Power: 3+2W; Material: Aluminum & toughened glass; Center Part: 3000K/4000K/6500K ; Peripheral: RGB; Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up; | ≥70 | 160lm±5% | |
| GL-BLR-3C-9W |  | LED Round Three-color Down Light; Size: Ø160mm; Cut-out: Ø140mm; Power: 6+3W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up. | ≥70 | 600lm±5% | |
| GL-BLR-3C-16W |  | LED Round Three-color Down Light; Size: Ø180mm; Cut-out: Ø160mm; Power: 12+4W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up. | ≥70 | 1050lm±5% | |
| GL-BLR-3C-24W |  | LED Round Three-color Down Light; Size: Ø240mm; Cut-out: Ø210mm; Power: 18+6W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up. | ≥70 | 1300lm±5% | |
| GL-BLS-3C-5W |  | LED Square Three-color Down Light; Size: 130*130mm; Cut-out: 110*110mm; Power: 3+2W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up | ≥70 | 160lm±5% | |
| GL-BLS-3C-9W |  | LED Square Three-color Down Light; Size: 160*160mm; Cut-out: 140*140mm; Power: 6+3W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up | ≥70 | 600lm±5% | |
| GL-BLS-3C-16W |  | LED Square Three-color Down Light; Size: 180*180mm; Cut-out: 160*160mm; Power: 12+6W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up | ≥70 | 1050lm±5% | |
| GL-BLS-3C-24W |  | LED Square Three-color Down Light; Size: 240*240mm; Cut-out: 210*210mm; Power: 18+6W; Material: Aluminum & toughened glass. Center Part: 3000K/4000K/6500K, Peripheral: RGB. Segmented color-changing: Centre part light up/Peripheral part light up/ All lamp light up | ≥70 | 1300lm±5% | |
| LED Recessed Panel Lights (NEW) | | | | | |
| GL-TCR-6W |  | LED round surface mounted lamp, 6w, lamp size Ø 120mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 340lm±5% | |
| GL-TCR-12W |  | LED round surface mounted lamp, 12w, lamp size Ø 170mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 700lm±5% | |
| GL-TCR-18W |  | LED round surface mounted lamp, 18w, lamp size Ø 225mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1300lm±5% | |
| GL-TCR-24W |  | LED round surface mounted lamp, 24w, lamp size Ø 300mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1650lm±5% | |
| GL-TCS-6W |  | LED square surface mounted lamp, 6w, lamp size 120 *120mm, 30*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 340lm±5% | |
| GL-TCS-12W |  | LED square surface mounted lamp, 12w, lamp size 170 *170mm, 60*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 700lm±5% | |
| GL-TCS-18W | | LED square surface mounted lamp, 18w, lamp size 225 *225mm, 90*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1300lm±5% | |
| GL-TCS-24W | | LED square surface mounted lamp, 24w, lamp size 300 *300mm, 120*SMD2835 San'an chip, IP22, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1650lm±5% | |
| LED Surface Panel Lights (NEW) | | | | | |
| GL-SMR-6W | | LED slim round surface mounted lamp, 6w, lamp size Ø 90mm*24mm, IP22, San'an Chip, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 360lm±5% | |
| GL-SMR-12W | | LED slim round surface mounted lamp, 12w, lamp size Ø 138mm* 24mm, IP22, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥70 | 750lm±5% | |
| GL-SMR-18W | | LED slim round surface mounted lamp, 18w, lamp size Ø 190mm*24mm, IP22, Sanan Chip, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1260lm±5% | |
| GL-SMS-6W | | LED slim square surface mounted lamp, 6w, lamp size 90mm*24mm, IP22, San'an Chip, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 360lm±5% | |
| GL-SMS-12W | | LED slim square surface mounted lamp, 12w, lamp size 138mm* 24mm, IP22, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥70 | 750lm±5% | |
| GL-SMS-18W | | LED slim square surface mounted lamp, 18w, lamp size 190mm*24mm, IP22, Sanan Chip, 30,000hrs operating life, AC220-240V input, 2 years warranty | ≥70 | 1260lm±5% | |

| LED Recessed Panel Lights (NEW) | | | | | |
|---------------------------------|---|---|-----------|-----------------|--|
| GL-THD03-8W |  | LED New Round Recessed Panel Lights, 8w, lamp size \varnothing 90mm*30mm, Cut-out size: \varnothing 70mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 600lm \pm 5% | |
| GL-THD03-16W | | LED New Round Recessed Panel Lights, 16w, lamp size \varnothing 145mm*30mm, Cut-out size: \varnothing 125mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1200lm \pm 5% | |
| GL-THD03-22W |  | LED New Round Recessed Panel Lights, 16w, lamp size \varnothing 170mm*30mm, Cut-out size: \varnothing 155mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1650lm \pm 5% | |
| GL-THD03-30W | | LED New Round Recessed Panel Lights, 30w, lamp size \varnothing 220mm*30mm, Cut-out size: \varnothing 200mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 2200lm \pm 5% | |
| GL-THD04-8W |  | LED New Square Recessed Panel Lights, 8w, lamp size 90mm* 90mm*30mm, Cut-out size: \varnothing 70mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 600lm \pm 5% | |
| GL-THD04-16W | | LED New Square Recessed Panel Lights, 16w, lamp size 145mm*145mm*30mm, Cut-out size: \varnothing 125mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1200lm \pm 5% | |
| GL-THD04-22W |  | LED New Square Recessed Panel Lights, 16w, lamp size 170mm*170mm*30mm, Cut-out size: \varnothing 155mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1650lm \pm 5% | |
| GL-THD04-30W | | LED New Square Recessed Panel Lights, 30w, lamp size 220mm*220mm*30mm, Cut-out size: \varnothing 200mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 2200lm \pm 5% | |
| LED Surface Panel Lights (NEW) | | | | | |
| GL-THD05-6W | | LED New Round Surface Mounted Panel Lights, 8w, lamp size \varnothing 90mm*27mm, IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-THD05-6W |  | LED New Round Surface Mounted Panel Lights, 16w, lamp size \varnothing 145mm*27mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-THD05-6W | | LED New Round Surface Mounted Panel Lights, 16w, lamp size \varnothing 170mm*27mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-THD05-6W | | LED New Round Surface Mounted Panel Lights, 30w, lamp size \varnothing 220mm*27mm, IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1260lm \pm 5% | |
| GL-THD06-6W | | LED New Square Surface Mounted Panel Lights, 8w, lamp size 90mm* 90mm*27mm , IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-THD06-6W |  | LED New Square Surface Mounted Lights, 16w, lamp size 145mm*145mm*27mm, IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 360lm \pm 5% | |
| GL-THD06-6W | | LED New Square Surface Mounted Panel Lights, 16w, lamp size 170mm*170mm*27mm, IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 750lm \pm 5% | |
| GL-THD06-6W | | LED New Square Surface Mounted Panel Lights, 30w, lamp size 220mm*220mm*27mm, IP42, Sanan Chip, 30,000hrs operating life, AC220-240V input, includes driver ,2 years warranty | ≥ 70 | 1260lm \pm 5% | |